

EARTH FAULT RELAY R201



FEATURES

- Numerical earth fault relay
- Two-stage setting for earth fault
- 5 selectable IDMT and definite times
- Circuit breaker failure protection
- Selectable fundamental or true RMS measurement
- Selectable 50 or 60 Hz frequency
- Programmable output contacts
- Non-volatile fault values recording up to 3 records
- Complies with IEC 60255 standard
- ANSI code: 50G, 51G, 50N, 51N, 50BF

SPECIFICATIONS

RATING

Rate Current In	: 5A
Frequency	: 50 or 60Hz
Burden	: <0.3VA at In
Thermal Withstand	: 4 x In Continuous

AUXILIARY SUPPLY

Supply Voltage	: 198 ~ 265VAC
Supply Frequency	: 50 or 60Hz
VA Rating	: 3VA max

ACCURACY

Protection Thresholds:	±3% or ±20mA whichever is greater
Time Delay	: ±3% or ±40ms whichever is greater

SETTING RANGES

Earth-fault Setting

I _o >	: 0.1A-10.0A(2% -200%), *(Variable steps 1)
kt _{lo} >	: 0.01 -1.00, *(Variable steps 2)
t _{lo} >	: 0.03 -100s, *(Variable steps 2)
I _o >Delay Type	: DT, NI3/10, NI1.3/10, VI, LI, EI
I _o >>	: OFF/0.1 -50A (2% -1000%), *(Variable steps 1)
t _{lo} >>	: 0.03 -100s, *(Variable steps 2)

OUTPUT CONTACTS

Rated Voltage	: 250VAC
Continuous Carry	: 5A (Cosφ=1.0)
Expected Electrical Life	: 10 ⁵ operations
Expected Mechanical Life	: 5 x 10 ⁶ operations
No of Output Contact	: 2

ENVIRONMENTAL CONDITIONS

Operating Temperature	: -10°C to 55°C
Humidity	: 5% to 95%, non-condensing

MECHANICAL


Mounting	: Panel mounting
Dimension (mm)	: 96(w) x 96(h) x 90(d)
Enclosure protection	: IP54 at the panel IP20 at the body
Approximate weight	: 0.65kg

*Variable Steps 1: step 0.05 (<10), step 0.1 (<100)


*Variable Steps 2: step 0.01 (<1), step 0.1 (<10), step 0.5 (<100)

IDMT CURVE


NORMAL INVERSE 3/10




NORMAL INVERSE 1.3/10




VERY INVERSE




LONG-TIME INVERSE






EXTREMELY INVERSE



TYPICAL APPLICATION DIAGRAM



CASE DIMENSION



ORDERING INFORMATION

MODEL	DESCRIPTION
R201-230A	Auxiliary Voltage 198~265 V AC, frequency 50 or 60Hz